

# P5® – LOSP AZOLE TREATED SOLID WOOD PRODUCTS MATERIAL DATA SAFETY SHEET



## SECTION 1: IDENTIFICATION OF THE PRODUCT AND OF THE COMPANY

Product Identifier	Not Available
Product name	P5® - LOSP Azole Treated Solid Wood Products
Synonyms	Not Available
Other means of identification	Not Available

**Relevant identified uses of the substance or mixture and uses advised against**

Used in residential, commercial and industrial construction and/or general purpose building.

### Details of the supplier of the safety data sheet

Registered company name	Shamrock Building Materials Inc)
Address	9115 SW Oleson Rd. Suit 300, Portland, OR 97223
Telephone	Toll Free (888) 742-6763
Website	www.shamrockbm.com
Email	Not Available

Emergency telephone number Not Available

Association / Organisation Not Available

Emergency telephone Not Applicable

## SECTION 2: HAZARDS IDENTIFICATION

### Classification of the substance or mixture

**NON-HAZARDOUS MATERIAL. NON-DANGEROUS GOODS**

### HAZARD RATINGS

		Min	Max
Flammability	0		
Toxicity	0		
Body Contact	1		
Reactivity	0		
Chronic	0		

0 = Minimum  
1 = Low  
2 = Moderate  
3 = High  
4 = Extreme

<b>Poisons Schedule</b>	Not Applicable
<b>Classification</b>	Not Applicable
<b>GHS label elements</b>	Not Applicable
<b>Hazard statement(s)</b>	Not Applicable
<b>Precautionary statement(s) Prevention</b>	Not Applicable
<b>Precautionary statement(s) Response</b>	Not Applicable
<b>Precautionary statement(s) Storage</b>	Not Applicable
<b>Precautionary statement(s) Disposal</b>	Not Applicable

## SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

**Substances** See section below for composition of Mixtures

CAS No	%[weight]	Name
Not Available	>98	Radiata pine wood
64743-95-6	<2	Impregnation solvent residuals
107534-96-3	<0.1	Tebuconazole
60207-90-1	<0.1	Propiconazole
52645-53-1	<0.1	Permethrin
136-53-8	<0.1	2-ethylhexanoic acid, zinc salt

In use, may generate wood dust (softwood).

THIS REPORT IS FOR THE TREATED WOOD PRODUCT ONLY



## SECTION 4: FIRST AID MEASURES

Description of first aid measures

<b>Eye Contact</b>	Hazard relates to dust or particles released by sawing, cutting, sanding, trimming or other mechanical finishing operations on the product. If the product comes in contact with eyes: Wash out immediately with water. If irritation continues, seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
<b>Skin Contact</b>	Brush off dust. Wash affected skin with soap and water after handling the material. In the event of abrasion or irritation of the skin seek medical attention.
<b>Inhalation</b>	If dust is inhaled, remove from contaminated area to fresh air. Encourage patient to blow nose to ensure clear of breathing passage. Drinking water may clear the throat. If irritation persists seek medical attention.
<b>Ingestion</b>	Unlikely to occur. Hazard relates to dust released by sawing, cutting, sanding, trimming or other finishing operations. Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Center or a doctor.
<b>General</b>	Recommended first aid facilities are for general construction / building work such as for cuts, abrasions and splinters. An eye wash station and hand washing facilities are also recommended.

### Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: FIREFIGHTING MEASURES

### Extinguishing media:

Water spray or fog.  
Carbon dioxide  
Foam.  
Dry chemical powder.

### Special hazards arising from the substrate or mixture:

**Fire Incompatibility** Avoid exposure to excessive heat and fire.

### Advice for firefighters:

#### Fire Fighting

Alert Fire Brigade and tell them location and nature of hazard.  
Use water delivered as a fine spray to control the fire and cool adjacent area.

#### Fire/Explosion Hazard

Combustible. Will burn if ignited. Whole wood products do not normally constitute an explosion hazard. Wood dust created by mechanical or abrasive processes may present an explosion hazard if a dust cloud contacts an ignition source.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

**Minor Spills**  
**Major Spills**

Pick up.  
Pick up or secure load if safe to do so.

# P5® – LOSP AZOLE TREATED SOLID WOOD PRODUCTS MATERIAL DATA SAFETY SHEET



## SECTION 7: HANDLING AND STORAGE

### Precautions for safe handling:

#### Safe handling

Use gloves when handling product to avoid splinters.

#### Other information

Keep dry

### Conditions for safe storage, including any incompatibilities:

#### Suitable container

Generally not applicable.

#### Storage incompatibility

Keep dry

Not regulated by USDOT.

Personal protection advice is contained in Section 8.

## SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

### General

Exposure and controls will relate primarily to dust created from abrasive or mechanical operations on the product. Wood dusts may be irritating to the eyes, skin and respiratory tract.

### Control parameters

#### OCCUPATIONAL EXPOSURE LIMITS (OEL)

No value set for the specific product however exposure standards exist for some components of the product as below.

Name	WES-TWA
	mg/m <sup>3</sup>
Radiata pine wood (as dust)	5
Impregnation solvent residuals	525
Tebuconazole	Not available
Propiconazole	Not available
Permethrin	Not available
2-ethylhexanoic acid, zinc salt	Not available

### Personal protection

<b>General</b>	Control exposure to wood dust if generated by mechanical ventilation to ensure that air borne wood dust levels are below exposure limits or wearing appropriate dust filter masks. Maintain good housekeeping to avoid accumulation of wood dust and waste.
<b>Inhalation</b>	Avoid inhalation of wood dust. Use a suitable air borne dust filter mask if working in confined area.
<b>Eyes</b>	Wear approved eye protection during mechanical operations such as cutting or machining where fine flying particles may be generated.
<b>Skin</b>	Suitable work clothing and light leather gloves for protection against splinters and abrasions. A barrier cream may help prevent drying of the skin and irritation. Launder work clothing after each day of work.
<b>Ingestion</b>	Unlikely to be a source of exposure. Avoid inhalation of wood dust and wash hands before meal breaks.

# P5® – LOSP AZOLE TREATED SOLID WOOD PRODUCTS MATERIAL DATA SAFETY SHEET



## SECTION 9: HEALTH EFFECTS

<b>General</b>	If workplace practices and controls noted in this report are followed, no health effects are expected. Wood dust may be irritating to the eyes, skin and respiratory tract. Wood dust may be a human carcinogen.
<b>Inhalation</b>	Wood dust may cause coughing, sneezing and other signs of respiratory tract irritation. Prolonged and repeated exposure to wood dust may cause bronchial asthma and other respiratory diseases.
<b>Eyes</b>	Particles or dust may cause irritation and be abrasive to eyes.
<b>Skin</b>	May cause dryness or mild irritation to skin.
<b>Ingestion</b>	Unlikely to be a source of exposure. May cause irritation to mouth and throat and abdominal discomfort.

## SECTION 10: PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

Appearance	Solid wood products in various sizes and pre-painted, May have a slight white spirit (hydro carbon solvent) odor. THIS REPORT IS FOR THE TREATED WOOD PRODUCT ONLY.
Physical state	Manufactured article
Density	Typically 0.4 to 0.5 kg/L (35 to 40 lb/cuft)
Solubility	Not applicable
Auto-ignition temperature	>200° C (>390° F)
Melting point	Not applicable
Flammability	Not applicable – product is combustible. See section 5.
Volatility	Not applicable

Disclaimer: The information contained herein is provided in good faith for general guidance on safe handling of P5 LOSP Azole Treated Solid Wood Products. However, no warranty is made, either express or implied, regarding the information or recommendations provided by Shamrock Building Materials, the accuracy of the information contained herein, or the results to be obtained from the use of such information. Any user must make their own determination and satisfy themselves that the information and recommendations given here are (i) suitable for intended process and purpose and (ii) in compliance with applicable environmental, health and safety regulations. For any additional information contact Shamrock Building Materials.

November 2017